

Why LG Digital Signage?

LG offers the greatest satisfaction to its customers in all business areas with trustworthy and innovative solutions. As the world leader in the global display market, LGE manufactures products with world class performance and design. Throughout the years the company has been developing innovative products satisfying customer requirements based on its long experience and know-how, and has been recognized for its trustworthiness and technological excellence.

LGE is also concerned about global environmental issues and is dedicated to bringing about solutions. Currently, 93,000 employees at 124 locations worldwide are devoted to the production of various display products and are tending to customized requirements for the world B2B market.

LGE will continuously provide the perfect solution for your business in the increasingly complex B2B market.

LG Display Solution Features IPS, Revolutionary Viewing • Excellent viewing angle from any perspective • Superior quality for outdoor images No fall-off in color accuracy at wide angles No blackening defect in outdoor environment No diversion in contrast ratio at wide angles No need of IR blocker or extra cooling system • Low screen temperature on Standard mode Flexible with digital signage environment Better image quality with no blackening • Minimized image distortion upon external pressure 24/7 Operation Various Usages LG Public Display Module has no time and spatial Usage Expansion restraints, and provides high durability and continuous quality even under 24/7 operational requirements. Integrated New Application

2012 Innovative LG Digital Signage Line-Up





2012 LG DIGITAL SIGNAGE LINE-UP (as of 1Q 2012)



47" (Direct LED)

800cd/m²

500,000 : 1

160W(Typ)

Easy Installation

Seamless bezel & Slim depth
 Low Power Consumption
 Anti Reflection Coating

Standard Display







	Direct LED	Edge LED		LCD				
	72WS70	WS10			VS20			
Inch	72F"	42F"	47F"	55F"	42F"	47F"	55F"	
Bezel Width	38.7mm	27.6mm	28.0mm	33.5mm	16.9mm	17.9mm	18.9mm	
Brightness	700cd/m ²	450cd/m ²	450cd/m ²		700cd/m ²			
Shine-out	No	No		No				
Portrait	Yes	Yes	Yes			Yes		
DCR	500,000 : 1	50,000 : 1			3,000 : 1			
Power Consumption	500W(Typ), 200W(SES)	115W(Typ), 80W(SES)	120W(Typ), 95W(SES)	140W(Typ), 110W(SES)	170W(Typ), 130W(SES)	180W(Typ), 130W(SES)	260W(Typ), 160W(SES)	
Special Features	*72" LED Large Screen Monitor *Local dimming Technology *Eco-Friendly *Smart Energy Saving	Eco-Friendly Smart Energy Saving Media Player Integrated Solution Stylish Design for Interior Decoration		Narrowest Bezel for Standard LCD Smart Energy Saving Media Player Integrated Solution				









					L(
	VS10		M3704C 47VL10		M4210L		
Inch	32"	42F"	47F"	65F"	37F"	47F"	42F"
Bezel Width	51.5mm	30.4mm	36.0mm	49.0mm	53.7 mm	36 mm	30.4 mm
Brightness	450cd/m ²	500cd/m ²	500cd/m ²	700cd/m ²	500cd/m ²	500cd/m ²	500cd/m ²
Shine-out	No				No	No	No
Portrait	Yes				No	Yes	Yes
DCR	10,000 : 1				10,000 : 1	3,000 : 1	3,000 : 1
Power Consumption	100W(Typ)	200W(Typ)	240W(Typ)	420W(Typ)	150W(Typ)	260W(Typ)	220W(Typ)
Special Features	High Scalability Easy Installation & Maintenance			ance	Super IPS Panel	Competitive Price for Enterprise market Eco-Friendly Easy remote management	Optimized Interface

High performance Intel platform CPU & Maximized Optional Value Media Player







	NC1000/2000	NC1100/2100	NA1100/2100	NA1000/2000		
	250mm(W) x 45mm(H) x 220mm(D) (Only Set)	250mm(W) x 45mm(H) x 220mm(D) (Only Set)				
	1.43kg (Only Set)	1.56kg (Only Set)				
CPU Intel® ATOM Proc (Dual Core)		Intel2® Celeron2® P4500 Processor Cache-L1/L2/L3 32K/256K/2M, 1.86 GHz	Intel2® Core™ i5-520M Processor 3M Cache, 2.40 GHz	Intel2® Core™ i7-620M Processor 4M Cache, 2.66 GHz		
	Nvidia MCP7A - ION integrated Graphic chipset		Intel2® QM57 Chipset			
	DDR3 1066 1024 MB SODIMM type, 1G(Option:2048MB,2G)	DDR3 SDRAM unbuffered 1066 1024MB SODIMM type, 1G (Option:2048MB, 2G)				
9	SSD 8 / 16 / 32GB	SSD 8 / 16 / 32 / 64GB				
	Windows XP Embedded Standard	Windows XP Embedded Standard				
	Realtek 10/100/1000Mbps	Intel2® 82577LM Gigabit(10/100/1000Mbps) Ethernet PHY				
Slot PC Part	HDMI out, USB 3ea, LAN (10/100/1000Mbps), PCI mini Express Card), HDMI out, USB 2ea, LAN (10/100/1000Mbps), PCI mini Express Card				
External Part	USB 2ea, SDPIF, D-SUB, Line out RS-232C, 4 in 1 Multi-card	USB 2ea, DP out, Mic in, D-SUB Line out, RS-232C, 4 in 1 Multi-card				
	Slot PC Part External	250mm(W) x 45mm(H) x 220mm(D) (Only Set) 143kg (Only Set) Intel® ATOM Processor 330 1.6GHz (Dual Core) Nivida MCP7A - ION integrated Graphic chipset DDR3 1066 1024 MB SODIMM type, 1G(Option:2048MB,2G) SSD 8 / 16 / 32GB Windows XP Embedded Standard Realtek 10/IOO/IOOOMbps Slot PC Part Chimic Express Clard (IO/IOO/IOOOMbps), Part Climic Express Clard External USB 2ea, SDPIF, D-SUB, Line out	250mm(W) x 45mm(H) x 220mm(D) (Only Set)	250mm(W) x 45mm(H) x 220mm(D) (Only Set) 250mm(W) x 45mm(H) x 220mm(D) (Only Set) 1.43kg (Only Set) 1.56kg (Only Set)		

Special Display



55WV70

3.4mm(left/top) / 1.9mm(right/bottom)

55F" (Direct LED)

800cd/m²

500,000 : 1

210W(Typ), 120W(SES, TBD)





Wide view with space saving
 Auto Scalor function for non-standard aspect ratio

Unique Application



Infinitely Expandable Video Wall Solution
 Super Narrow Bezel : 5.3mm(Bezel to Bezel)
 Anti Reflection Coating



	То	uch	Semi-Outdoor	Outdoor	
	M4716T	/ M4214T	47VX30MF / 47VX30MS	47WX50MF	
nch	47F"	42F"	47F"	47F"	
	36.1mm	32.5mm	11mm (Panel)	11mm (Panel)	
Brightness	400cd/m ²		700cd/m²	2000cd/m²	
	No		Yes	Yes	
Portrait	Yes		Yes	Yes	
DCR	3,000 : 1		3,000 : 1	500,000 : 1	
Power Consumption	260W(Typ)	211W(Typ)	260W(Typ)	350W(Typ)	
Special Features	Infrared multi-touch te IR matrix touch - 2 poi		High Visibility • Reliability Easy to customize (Open Frame) Only 47VX30MF	2,000nit Shine-Out Auto cooling & Brightness control Easy to customize (Open Frame)	

Easy and intuitive software that allows even the novice can operate conveniently







	SuperSign Elite-s	SuperSign Elite-w	SuperSign Elite-w lite	
Player Connection	Under 30 EA	1,000 EA possible		
Distribution Server	Single server	Multi server		
Multi-User Support	Single user	Multi user creation Multi users can use at the same time Single user		
Role Separation by User	Single role-manager	Possible to grant authority by mixing more than 20 different authority such as designer, scheduler, and manager		
Content Editor	PC based editor	Web and PC based editor have the same number of functions		
Content Library	25 media and 6 categories	Categorization by category, Categorization by folder		
Dashboard	N/A	Update System information and new content information		
Distribution Manager	N/A	Adopted distribution page. Possible to distribute schedule, media. Possible to monitor the distribution status. Distribution by reservation.		

EzSign TV

- •COST-EFFECTIVE -No media player
- •FAST & EASY -Edit content quickly and easily
- •CUSTOMIZED TO YOUR NEEDS -Signage content can be specific to your business

•SLEEK DESIGN

- -Enhance the quality of the customer experience
- -Pick and choose from an array of template designs



		North America	CH		
	LT560E	LV355B	LD452B	LT560E	LD455B
Inch	32F", 37F", 42F", 47F"	32", 37F", 42F", 47F", 55F"	32", 42F", 47F"	32", 42F", 47F"	32F", 42F", 47F"
Туре	LED	LED	LCD	LED	LCD
Resolution	1366 X 768(32), 1920 X 1080(37/42/47/55)	1920 X 1080	1366 X 768(32), 1920 X 1080(42/47)	1366 X 768(32), 1920 X 1080(42/47)	1920 X 1080
Special Features	Wifi Updating Smart Scheduling HD Dvix Free Template	Cost Effective Fast & Easy Editing Customized To Your Business Sleek Design Various Template Designs	Cost Effective Fast & Easy Editing Customized To Your Business Sleek Design Various Template Designs	Wifi Updating Smart Scheduling HD Dvix Free Template	Cost Effective Fast & Easy Editing Customized To Your Business Sleek Design Various Template Designs









	EU/	CIS	ASIA		
	LT660E	LD320B	LT640E	LD462B	
Inch	32", 42F"	32", 42F"	32", 37F", 42F"	32F", 37F", 42F", 47F"	
Туре	LED	LCD	LED	LCD	
Resolution	1366 X 768(32), 1920 X 1080(42)	1366 X 768(32), 1920 X 1080(42)	1366 X 768(32), 1920 X 1080(37/42)	1920 X 1080	
Special Features	Wifi Updating Smart Scheduling HD Dvix Free Template	Cost Effective Fast & Easy Editing Customized To Your Business Sleek Design Various Template Designs	Wifi Updating Smart Scheduling HD Dvix Free Template	Cost Effective Fast & Easy Editing Customized To Your Business Sleek Design Various Template Designs	









	IVI	LA	50	SCA		
	LT640E	LD462B	LT560E	LD460B		
Inch	32", 37F", 42F"	32F", 37F", 42F", 47F	32", 37F"	32F", 42F"		
Туре	LED	LCD	LED	LCD		
Resolution	1366 X 768(32), 1920 X 1080(37/42)	1920 X 1080	1366 X 768(32), 1920 X 1080(37)	1920 X 1080		
Special Features	Wifi Updating Smart Scheduling HD Dvix Free Template	Cost Effective Fast & Easy Editing Customized To Your Business Sleek Design Various Template Designs	Wifi Updating Smart Scheduling HD Dvix Free Template	Cost Effective Fast & Easy Editing Customized To Your Business Sleek Design Various Template Designs		