

TOUCH DISPLAY

M4214T M4716T

•Infrared Multi-Touch Technology •Built to fit in trendy indoor environments



SPECIFICATION

PANEL

Screen Size : 42" Aspect Ratio : 16 : 9

Native Resolution : 1920 x 1080 (FHD)

Brightness: 400cd/m² Contrast Ratio : 1,300:1, 3,000:1 (DCR) Viewing Angle (H x V) : 178 x 178

Response Time : 10 ms (G to G)

AUDIO

Audio Power: 20W (10W x 2) Speaker On/off : Yes Clear Voice II : Yes Sound mode : Standard / Music / Cinema

/ Sports / Game / User

CABINET

Bezel Width: 32.5 mm

Touch

Touch type : IR (Infrared Rasys) LED Available object size for touch : 7 mm (Touch), _8 mm (Drawing) Response Time : 13.5 ms Accuracy : 5mm Operating Systme Support : Windows XP / Vista / 7

MULTI-TOUCH TECHNOLOGY

infrared multi-touch technology. This makes information to user.



TRENDY DESIGN

Touch monitor supports various applications with For retail, hospitality, airports, bus terminals, exhibition, restaurants, conference rooms, stock exchanges and with its simple and trendy design.



eZ-Net Manager

eZ-Net manager lets the user control monitors which are installed in remote areas through ethernet. So you can check the status of monitors and change the input and volume, even update the firmware from server.



Dimension

